

GLRM

Multi-band RTK
rover with tilt
compensation




Versatile



PHONE AND TABLET



MINIPOLE



POLE AND TRIPOD

All constellations All frequencies Tilt compensation Jamming proof Spoofing proof

Ultra compact and lightweight

Rugged IP67 aluminium case

Magnetically attached to the mobile device

Wireless charging of the mobile device

Precise and fast centimeter accuracy, fix in 2 sec.

Best in class triple frequency high-gain antenna

Made in Austria

Positioning

GNSS tracked

Galileo E1, E5a, E5b, E6
GPS L1C/A, L1C, L2C, L2P(Y), L5
BDS B1I, B2I, B3I, B1C, B2a, B2b
GLONASS G1, G2, G3
QZSS L1C/A, L1C, L2C, L5
SBAS L1C/A
NavIC L5

Channels

1406

Precision

RTK

H: 7 mm + 1 ppm, V: 14 mm + 1 ppm

PPP

H: 50 mm + 1 ppm, V: 100 mm + 1 ppm

Tilt compensation

< 20 mm at 60°

Mechanical

Receiver size L × B × H, weight

95 × 64 × 12.5 mm
115 g

Receiver + mobile antenna, weight

198 × 64 × 49 mm
160 g

Receiver + pole antenna, weight

110 × 70 × 65 mm
260 g

Operating temperature

-40°C to +85°C

Ingress Protection

IP67

Connectivity

BLE 5.3, Serial

Electrical

Battery

LiPo 2000 mAh

Operation


10 hours

Charging

USB-C, 5V, 3A

Errors and technical modification subject to change.

Available colors



Contact us

office@general-laser.at

general-laser.at

+43 1 890 2002

