



# α-GEO

## L600

### GNSS receiver



## PRECISION

you can trust



IMU TILT



UHF RADIO



WEBUI



FULL GNSS

#### Performance specification

Satellite signals tracked simultaneously	GPS: L1, L1C, L2C, L2P, L5
	GLONASS: L1C/A, L1P, L2 C/A, L2P, L3
	BEIDOU: B1, B2, B3, B1C, B2a, B2b
	GALILEO: E1, E5a, E5b, E6c, AIRBOC
	QZSS: L1, L2C, L5
	SBAS: WAAS, EGNOS, MSAS, GAGAN, SDCM
	IRNSS: L5
Channels	965 tracking Channels
Cold start	<60 s
Hot start	<15 s
Positioning output rate	1Hz - 20Hz
Signal Reacquisition	<1s
RTK Initialization time	<10s
Initialization Reliability	>99.99%
Time accuracy	20 ns

#### Positioning<sup>1</sup>

Code differential GNSS positioning	Horizontal: 0.25 m + 1 ppm RMS
	Vertical: 0.50 m + 1 ppm RMS
	SBAS differential positioning accuracy: typically <5m 3DRMS
Static GNSS surveying	Horizontal: 2.5 mm + 0.5 ppm RMS
	Vertical: 5 mm + 0.5 ppm RMS

#### Real Time Kinematic Surveying

Single Baseline < 30 KM	Horizontal: 8 mm + 1 ppm RMS
	Vertical: 15 mm + 1 ppm RMS
Network RTK <sup>3</sup>	Horizontal: 8 mm + 0.5 ppm RMS
	Vertical: 15 mm + 0.5 ppm RMS

#### HARDWARE

PHYSICAL	
Material	Magnesium alloy
Dimensions	160mm * 52mm (without bottom connector 74mm)
weight	≤1.0 Kg
Operating temperature	-40°C to +75°C
Storage temperature	-55°C to +85°C
Protection IP	IP67 dust proof, protected from 30min immersion to depth of 1m
Shock	Survive a 2m pole drop onto concrete
Vibration	MIL-STD-810G
Humidity	100%, condensing

1- Precision and reliability may be subject to anomalies due to multipath, obstructions, satellite geometry and atmospheric conditions. The specifications stated recommend the use of stable mounts in an open sky view, EMI and multipath clean environment, optimal GNSS constellation configurations. Base lines longer than 30 km require precise ephemeris and occupations up to 24 hours may be required to achieve the high precision static specification.

2- Depends on SBAS system performance

3- Network RTK PPM values are referenced to the closest physical base station and depends on network performances.

**TOPOTRADE**  
Strada IACOB NEGRUZZI  
nr. 44, 011094, Bucuresti-1  
(+40)722 620 305  
e-mail: [topotrade@yahoo.com](mailto:topotrade@yahoo.com)  
[www.topotrade.ro](http://www.topotrade.ro)

#### ELECTRICAL

Power: 9~24 V DC external power input on 5 pin LEMO port  
Support USB Type-C fast charging  
Internal 6800mAh lithium-ion battery

Battery Life	Rover Mode: 12 hours
	Base Mode: 7 hours
	Static Mode: 15 hours

#### Communication & Data Storage

I/O interface	
LEMO port (5pin)	Supports power input, serial port control, and external radio communication
USB Type-C port	Data download / Charging
Sim card slot	Supports Nano-SIM
Antenna port	UHF antenna interface
Radio modem (optional)	
Transmit power	1/2 w switchable, Work range is longer than 4km
Frequency band	410MHz~470MHz; supports to set the frequency

Supports retransmitting correction from CORS; compatible with other brands

Cellular	
Integrated full frequency multi band 4G modem, supports WCDMA/CDMA2000/TDD-LTE/FDD-LTE	
WIFI	
802.11 b/g standard, access point & client mode, supports access to hotspot for correction transmission	
Bluetooth	
Fully integrated Bluetooth V4.0, range ≤ 50m	
Data format	
RTCM2x, RTCM3x, CMR & CMR+, sCMRx	
Dat, RINEX, NMEA outputs: Support VRS, FKP, MAC, NTRIP	
storage	
8GB internal memory, supports cyclic storage; with ability to collect over one year raw observation based on 5 seconds interval	

#### Others

System integration	
OS system:	Intelligent LINUX operating system
Tilt Compensation	IMU up to 60° (Calibration free)
Relay station	CORS relay, Radio relay
Supported controllers	All android devices with supported software
Design	
button	Power key
Indicator	Power indicator, data link indicator, satellite indicator, Bluetooth indicator
Voice	Intelligent voice prompts
WEBUI	Support WEBUI configuration

GUANGZHOU ALPHA GEO-INFO CO., LTD  
address: Room 601, Building No.1, Gaopu Road No.68, Tianhe District, Guangzhou 510630, Guangdong, China  
[www.alphageo-info.com](http://www.alphageo-info.com)  
email: [alphageo@aliyun.com](mailto:alphageo@aliyun.com)  
phone: +8618565149475

# **α-GEO**

**ULTIMATE PERFORMANCE  
OUTSTANDING INNOVATION**

**ONE SOLUTION**

**TOPOTRADE**  
Strada IACOB NEGRUZZI  
nr. 44, 011094, Bucuresti-1  
(+40)722 620 305  
e-mail: [topotrade@yahoo.com](mailto:topotrade@yahoo.com)  
[www.topotrade.ro](http://www.topotrade.ro)

## **L600**

### **GNSS receiver**

L600 is a compact new generation of smart GNSS receiver designed for any surveying project using the latest GNSS technology. This receiver is equipped with all modern required connectivity modules: Bluetooth, Internal radio, WIFI & 4G modem. 6800mAh Built-in battery, IMU tilt technology and WebUI are other latest technologies used in L600 receivers.

### **Multi constellation**

L600 with its 965 channels new generation full GNSS chipset & ability to support multiple satellite constellation including GPS, GLONASS, BEIDOU, GALILEO, QZSS, SBAS and IRNSS provides precise and accurate spatial data for all users around the world.




### **WiFi and WebUI**

L600 serves as a WIFI hotspot, so users can easily access, manage the status, set the configuration or download static and PPK raw data through advanced WebUI using computer, smartphone or other electronic devices with WIFI support without any need to third party software or cable.



### **IMU Tilt Sensor**

L600 is equipped with a fast initialization, calibration free & immune to magnetic interference Inertial Measurement Unit (IMU). All users can use this technology to collect or stakeout topo points up to 60°.



### **GSM & UHF radio**

A fast internet connection is guaranteed with a built-in 4G module that accelerates receiving correction data using all telecommunication signals and bands. L600 comes with an integrated Tx/Rx internal UHF radio that ranges from 410 MHz to 470 MHz with selectable frequency providing ability to connect and collect accurate real time data in Base/Rover mode.



### **Battery & Power**

L600 is delivered with an internal large capacity 6800mAh lithium-ion internal battery supporting USB type-C fast charging which allows users to work for more than 9 hours in daily field work.



### **IP67**

Choosing a small, light but professional, rugged GNSS receiver has always been a concern among professional surveyors. L600 with its high quality magnesium alloy body provides such advantages without decreasing quality or notable increase in price.



### **Working mode**

Every surveyor needs to operate and choose suitable working method based on project requirements and required accuracy. In order to work in such condition users will need a device to be able to work in different modes such as Static, Network RTK, UHF RTK, PPK & etc. L600 is offering all you need in a package!

