

PNHLR/G Horizontal Rotary Laser, pendulum leveling (SKU no. 205-PNHLR and 205-PNHLG)

Features

- Choose between red or green beam pendulum laser
- Very rugged against temperature variations
- Stable and robust leveling technique
- Inexpensive and reliable rotary laser
- Red beam only: Horizontal scanning functions ideal for composition floors and interior finishing. Green beam: even without scanning very well visible.

Technical Data

Leveling accuracy	$\pm 3 \text{ mm}/30 \text{ m}$
Leveling range	$\pm 4^\circ$
Working range	Up to 500 m radius with detector
Laser Class	2 (red: 635 nm, green: 520 nm)
Power supply	Lithium-Ion batteries (20 h)
Operating temperature	-10°C to $+45^\circ\text{C}$
IP protection	IP55
Rotary speed	300, 600, 1000 rpm
Dimensions	215 mm (length) x 150 mm (width) x 156 mm (height)
Weight	2.0 kg

Application

For all types of construction work interior and leveling, e.g., laying composition floors, depth control for excavators, fundamentals, walls, height control, landscaping

Scope of delivery

- Rotary Laser PNHLR (red) or PNHLG (green)
- Rechargeable Lithium-Ion battery and charger
- Target
- Laser glasses
- Transportation case
- Instruction manual

Get an optimum working range with our universal detector PNLUD14 (page 8) which receives rotary and line laser beams! More benefit for your customers: One detector - both laser types.

Service

Service directly at proNIVO! Our qualified service center performs repairs and maintenance of this instruments. You save cost and time.

We offer tripods, rods and other accessories. Have a look in our tripod catalog and ask for your offer!

