

# **REACH RX**

Multi-band network RTK rover

## Key features

- Tracks GPS/QZSS L1C/A, L2C, GLONASS L1OF, L2OF, BeiDou B1I, B2I, Galileo E1-B/C, E5b
- Gets a fix in 5 seconds
- Centimeter accuracy
- Easy to set up: just add NTRIP
- Comes with the ReachView 3 app
- Pocket-sized and lightweight
- 16 hours on 1 charge
- IP68



## **REACH RX**

#### Technical specifications

#### **POSITIONING**

recision RTK	H:7mm+1ppm
	V: 14 mm+1 ppm
	~5 s typically
Signal tracked	GPS/QZSS L1C/A, L2C,
	GLONASS L10F, L20F,
	BeiDou B1I, B2I,
	Galileo E1-B/C, E5b
ls	184
	5 Hz
	RTK

#### CONNECTIVITY

Communication interface	Bluetooth 4.2
Ports	USB Type-C
Input data format	RTCM3
Input data protocol	NTRIP
Position output	NMEA

#### **MECHANICAL**

Dimensions	172x51x51 mm (6.77x2.00x2.00 in)
Mount	5/8"-11UNC
Mount	5/8 -11UNC
Weight	250 g (8.81 oz)
Ingress protection	IP68 (maximum depth of 1.5 meters up to 30 minutes)
Operating t <sup>o</sup>	-20 to + 65 °C

#### **ELECTRICAL**

Autonomy	Upto 16 hrs
Battery	Li-Ion 5200 mAh, 3.6 V, 18.72 Wh
Charging	USB Type-C, 5 V, 2 A
Certification	FCC, CE, IC

#### More information about Reach RX



#### Emlid Software and services

#### **Emlid Studio**

Easy-to-use free software to simplify your post-processing workflow.



#### ReachView 3

Android & iOS survey app for data management.



#### **Emlid NTRIP Caster**

Pass corrections between your RTK GNSS receivers over the Internet.



### CE FC

#### YOUR LOCAL DEALER

