



PNSL Optical levels (SKU no. 205-PNSL-24 and 205-PNSL-32)

Features

- Models with 24x and 32x magnification
- Light and compact
- Superior optics
- Magnetisch gedämpfter, automatischer Kompensator
- Endless horizontal drive
- High precision level

Technical data		
Magnification	24x	32x
Leveling accuracy 1.6 mm	at 45 m	at 75 m
Working range	90 m	120 m
Objective aperture	32 mm	36 mm
Field of view	1° 25'	1° 25'
Minimum focus	0.3 m	0.3 m
Horizontal circle	1°/1 gon	1°/1 gon
Thread	5/8"x11	5/8"x11
Weight without case	1.7 kg	1.7 kg



Application

For all precision leveling tasks in the field, e.g. building patios, houses and baseplates, for landscaping, excavation height control, survey work on the jobsite and in the field

Scope of delivery

- Optical level
- Transportation case
- Plumb
- Cord
- Adjustment tool
- Allen wrench key
- Instruction manual

Service

Our technicians perform the calibration, adjustment and repairs of your optical levels. We offer a base and full service according to the customers' wishes. Please contact us!

You find more information on our data sheets.

Offer your customers a levelling set with tripod and rod! Ask for your best set price. You find suitable products in our tripod and accessories catalogs. We will tell you our recommendations!