

SATELLINE® -EASy Pro

Wireless World – Local Solution

SATELLINE-EASy Pro is an IP67 (NEMA 6) classified UHF radio modem with a high power (up to 25 or 35 W) transmitter and wide 70 MHz tuning range. It was designed for easy mobile use in demanding field conditions. According to the IP67 standard, the casing and connectors of the SATELLINE-EASy Pro are waterproof and secured against dust.

In addition to the high output power and wide tuning range, the channel spacing is also selectable to be 12.5, 20 or 25 kHz. The SATELLINE-EASy Pro is equipped with a Liquid Crystal Display (LCD) and a keypad, used to indicate the current operating status, as well as for changing the operating channel and power level of the radio modem.

| |
|-------------------|
| VHF with NMS |
| UHF with NMS |
| UHF |
| Licence Free |
| IP67 |
| Customer Specific |



With SATEL radio modems, setting up a local data transfer network is quick and cost effective. Your wireless network is independent and free of operator services. The cost of operation is either free of charge or fixed, depending on the frequency used. SATELLINE radio modems are type-approved in over 50 countries. For the latest information, please visit our website www.satel.com.

SATELLINE radio modem networks are flexible, easy to expand and can cover a wide variety of solutions from simple point-to-point connections to large networks comprising hundreds of modems. Even for expanded networks, only one operating frequency is required.

SATELLINE radio modems are always on line, and provide reliable, real-time data communications over distances ranging from tens or hundreds of metres up to around 80 kilometres. Thanks to a store and forward function, any radio modem in a network can be used as a master station, substation and / or repeater.



Heavy-duty tool for outdoor use

SATELLINE-EASy Pro is an IP67 classified UHF radio modem with a high power (up to 25 or 35 W) transmitter, wide 70 MHz tuning range (403 ... 473 MHz) in one hardware and selectable channel spacing.

SATELLINE-EASy Pro is particularly well suited for mobile field applications (land surveying, for instance) under varying weather conditions. Due to the high transmitting power, connection distances more than 80 kilometres can be covered in favourable conditions.

With the Liquid Crystal Display (LCD) the user can monitor the current operating status (frequency, channel number) as well as condition (power level, voltage level, field strength) of the radio modem.

SATELLINE-EASy Pro is compatible with SATELLINE-EASy and -3AS family products too.

Dependable data transfer

In the SATELLINE-EASy Pro the error rate is minimized by means of advance checking and correction of the data packets. In Forward Error Correction (FEC), the data packets are split in several blocks. The radio modem adds correction information inside the blocks during transmission.

In a SATELLINE-EASy Pro network, any substation can function as a repeater, too. In this operating mode (store and forward), the radio modem receives a message, buffers the received data, and transmits it further to another substation, using the same radio channel as in reception.

SATELLINE-EASy Pro features embedded Message Routing software, which takes care of routing messages across a radio modem network automatically after proper settings have been made. Communication is completely transparent, which makes Message Routing directly compatible with most user protocols.

Expert's help always at hand

With an experience of over twenty years, SATEL Oy has grown to one of the leading radio modem manufacturers in the world. As a result of our persistent and innovative work in both product design and international marketing, we now possess extremely large selection of radio modems, and operate through an extensive and skilled distributor network all over the world. We have also accumulated a considerable amount of know-how in different radio modem applications. So, whatever your application is, do not hesitate to ask for expert's help whenever needed.

SATELLINE radio modems have been used, for example, at airports and in waterworks and electricity plants for different monitoring and control applications, as well as to set up location data based fleet management systems in cities. For further information about our products and their applications, please see our home page www.satel.com or contact your local dealer.

Manufacturer:



SATEL Oy
Meriniitynkatu 17, P.O. Box 142,
FI-24101 Salo, FINLAND

Tel. +358 2 777 7800 info@satel.com
Fax +358 2 777 7810 www.satel.com

Technical specifications SATELLINE-EASy Pro

SATELLINE-EASy Pro complies with the following international standards: EN 300 113-1, -2, EN 301 489-1, -5, IEC 60950 and FCC CFR47 section 90.

TRANSCIVER

| | |
|---------------------------|------------------------------------|
| Frequency Range | 403...473 MHz |
| Tuning Range | 70 MHz |
| Channel Spacing | 12.5 / 20 / 25 kHz (SW selectable) |
| Frequency Error Tolerance | < 1 kHz |
| Type of Emission | F1D |
| Communication Mode | Half-Duplex |

TRANSMITTER

| | |
|-------------------------|--|
| Carrier Power | 10, 20, 25 or 35 W / 50 ohm (Default) 5, 10, 20 or 25 W / 50 ohm (Option *) |
| Carrier Power Stability | (+ 2 dB / - 3 dB) |
| TX Duty Cycle ** | 100 % (22 °C / 35 °C) 40 % 35 W 20 min / 13 min no limit 10 W no limit / 50 min no limit |

RECEIVER

| | |
|------------------------------|---------------------------------------|
| Sensitivity | < -114 dBm (BER < 10 E-3) *** |
| Co-channel Rejection | > -12 dB |
| Adjacent Channel Selectivity | > 47 dB @ 12.5 kHz / > 52 dB @ 25 kHz |
| Intermodulation Attenuation | > 60 dB |
| Spurious Radiation | < 2 nW |

DATA MODEM

| | |
|-------------------------------|----------------------------|
| Interface | RS-232 |
| Interface Connector | Waterproof IP67, 8-pin ODU |
| Data Speed of RS Interface | 300 – 38400 bps |
| Data Speed of Radio Interface | 19200 bps (25 kHz) |
| | 9600 bps (12.5 / 20 kHz) |
| Data Format | Asynchronous RS-232 |

GENERAL

| | |
|-------------------------------|--|
| Operating Voltage **** | +9 ... +16 Vdc |
| Operating voltage feeding | 4-pin ODU MINI-Snap Size 1 |
| Power Consumption (average) | 1.8 W typical (Receive) |
| | 120 W typical (Transmit 35W output power) 100 W typical (Transmit 25W output power) |
| | 0.4 W typical (Sleep State) |
| Temperature Range - Operating | -25 °C ... +55 °C |
| | -40 °C ... +75 °C (absolute minimum / maximum) |
| - Storage | -40 °C ... +85 °C |
| Antenna Connector | TNC, 50 ohm, female |
| Construction | Aluminium Enclosure |
| Size H x W x D | 189 x 138 x 71 mm (with connectors) |
| Weight | 1420 g |
| IP Classification | IP67 (NEMA 6) |

Values are subject to change without notice.

* Limited output power is available as an order option.

** If high output power is used continuously or with a high duty cycle, the equipment generates excess heat. The output power is automatically decreased when necessary to prevent overheating. Typical operating times are shown in the chart with different output powers and duty cycles @ 22°C and 35°C.

*** Depends on receiver settings.

**** ≥ +12 Vdc @ 35 W output power

Distributor:

TOPOTRADE
Strada IACOB NEGRUZZI
nr. 44, 011094, Bucuresti-1
(+40)722 620 305
e-mail: topotrade@yahoo.com
www.topotrade.ro